

The semi-automatic solution with top price/performance ratio



Characteristics

Ring diameters:	50 cm	90 cm	125 cm	160 cm	200/250 cm
Standard film quality:	23 m μ	23 m μ	23 m μ	23 m μ	23 m μ
Film reel dimensions:	100 mm	100, 170 mm	100, 170, 250 mm	100, 170, 250 mm	100, 170, 250 mm
Max. ring speed:	350 rpm	140 rpm	70 rpm	60 rpm	50 rpm
Power supply:	230 V	230 V	230 V	230 V	230 V
Power consumption:	0.26 Kw	0.31 Kw	0.48 Kw	0.52 Kw	0.55 Kw
Inverter / PLC:	Omron	Omron	Fuji / Omron	Fuji / Omron	Fuji / Omron

Advantages

- CE certified
- Proven quality with competitive price
- Easy operation, simple maintenance
- In various inner ring diameters available
- Double film reel dispenser
- Safety foot switch
- Ring protection
- Adjustable stretch film tension
- Adjustable ring speed
- Various optional features, i.e.
 - Automatic film cutter
 - Top press

Chart of types model FV300

Item No.	Model	Inner diameter
31.3001	FV300/50	50 cm
31.3002	FV300/90	90 cm
31.3003	FV300/125	125 cm
31.3004	FV300/160	160 cm
31.3005	FV300/200	200 cm
31.3006	FV300/250	250 cm