

Manual sealless steel strapping tool



Characteristics

Strapping qualities:	Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	widths 12.7 – 19.0 mm / ½ – ¾"
thicknesses	0.50 – 0.58 mm / .020 – .023"
Weights:	3.9 kg / 8.9 lbs Normal-version 4.3 kg / 9.5 lbs TW-version
Average seal strength:	approx. 80 %
TW-version available:	Torque wrench tensioning system
Suspension (Optional):	Bolt and grip ball for horizontal applications; have to be ordered separately Suspension bracket for vertical applications; has to be ordered separately

Advantages

- Handy light weight sealless combination tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals
- Thanks to its weight of 3.9 kg / 8.6 lbs only, it is very suitable for horizontal applications
- The consistency of the seal efficiency of the sealless joint is very high and as a general rule it is higher than joints using a separate seal

Chart of types model A335

Item No.	Model	Ultraflex max. 1100 N/mm ² / 160'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.2770	A335/12.7/0.50-0.58	12.7	1/2"	0.50-0.58	.020-.023
13.2780	A335/13/0.50-0.58	13		0.50-0.58	.020-.023
13.2790	A335/16/0.58	16	5/8"	0.50-0.58	.020-.023
13.2810	A335/19/0.58	19	3/4"	0.50-0.58	.020-.023

Chart of types model A335 with torque wrench tensioning system

Item No.	Model	Ultraflex max. 1100 N/mm ² / 160'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.2771	A335/12.7/0.50-0.58/TW	12.7	1/2"	0.50-0.58	.020-.023
13.2781	A335/13/0.50-0.58/TW	13		0.50-0.58	.020-.023
13.2791	A335/16/0.58/TW	16	5/8"	0.50-0.58	.020-.023
13.2811	A335/19/0.58/TW	19	3/4"	0.50-0.58	.020-.023

TW = Torque wrench tensioning system

Accessories

A33.4101	Bolt for horizontal applications (in combination with grip ball N4.1116)
N4.1116	Grip ball for horizontal applications (in combination with bolt A33.4101)
A33.0113	Suspension for vertical applications